

ACOUSTIC DOOR

AS-28-PAN(ii)

TECH SHEET AS-28-PAN(ii)

Issue: 30-07-2010

60 minute fire rated 28 Rw single acoustic / smoke / fire door

DESCRIPTION

Pyropanel AS-28-PAN(ii) is a 28 Rw, 1 hour fire rated 48mm single leaf acoustic door that utilises a Raven Products RP47 perimeter seal and a RP99 bottom seal.

APPLICATIONS

Ideal for unit entry applications or anywhere that requires 60 minutes of fire resistance and an acoustic rating of 28 Rw.

FEATURES

Acoustic Rating

- 28 Rw (28 STC)

Test Certificate number

- TL373(d)

Fire Resistance

- FRL -/60/30

Door Configuration

- Single leaf hung in steel or timber frame.

Perimeter Seal

- Raven RP47

Bottom Seal

- Raven RP99

Thickness

- 48mm (Nominal)

Size

- Maximum Size - 2420 x 1020 or 2200 x 1120 (-/60/30)

Hinges

- Minimum 3 steel hinges

Frame

- Pyropanel KDHW timber or packed pressed metal frame

Finish



- MDF as standard

OPTIONAL EXTRAS

- Pre-hung in steel or timber frame
- Ply, Veneer, Steel or Laminate facings
- Vision panels - 300 x 200 or 600 x 100mm.
- Kick Panels of 1mm Stainless Steel to selected height
- Meets the BCA requirement for a smoke door.

INSTALLATION

Door frame must be tightly sealed against wall structure using Pyropanel Multiflex or approved alternative fire and acoustic sealant. Metal door frames will require packing with Pyropanel FR board, Fire rated plaster, concrete or mortar to achieve desired acoustic rating.



HOW TO SPECIFY

“Door to be a Pyropanel AS-28-PAN(ii) acoustic door with -/60/30* FRL, installed into a Pyropanel Fire rated timber / packed metal* door frame”

* denotes example—delete, change or specify as required



Protecting Life and Property

Pyropanel Developments Pty Ltd
122-124 Beresford Rd, Lilydale, VIC, 3140
Ph: (03) 9739 3100 Fax: (03) 9739 3115
Email: sales@pyropanel.com.au
Web: www.pyropanel.com.au

Distributed by:



Australian Commercial Doors Pty Ltd
P: 03 9720 5766
F: 03 9720 5388
sales@acddoors.com.au